

# CODEx

# COMPACTDRIVE<sup>®</sup>

CA08 - 1024

## MAKING YOUR WORK FLOW

Like its predecessors, the Compact Drive™ is designed to support the challenging demands of creative professionals and is backed by Codex world-class support while utilising the latest PCIe-based flash to deliver unrivaled performance for professional applications and feeds seamlessly into Codex's industry-standard workflows.

The Compact Drive Adapter provides compatibility with Capture Drive solutions and a cost-effective Compact Drive Reader is also available.



## SPECIFICATIONS

Interface	PCIe
Capacity	1 TB
Dimensions [W x D x H]	45 x 77 x 9.8mm (1.8" x 3" x 0.4" approx)
Weight	85g
Operating Temperature	0°C ~ 70°C (32°F ~ 158°F)
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
Consumption (at 8Gbps)	6W
Transfer Speed	Up to 20Gb/s read
Insertion/Removal Durability	10,000 actions
Shock Resistance	(1/2 sine pulse, 0.5ms) - 1500G
Vibration Resistance	(7~800Hz)- 3.08 Grms
Warranty	1-year limited warranty
Product Code	CX.0001002

## HIGHLIGHTS

- Engineered to the highest performance standards.
- 1 TB Capacity.
- Up to 20Gb/s read.
- Optimised for performance.
- Advanced thermal design.



CODEx COMPACT DRIVE READER



IN-CAMERA RECORDING WITH ALEXA MINI LF



CODEx CAPTURE DRIVE ADAPTER FOR COMPACT DRIVE

For further information visit [codex.online/products/media/compact-drive](https://codex.online/products/media/compact-drive)

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical or otherwise, without the prior written permission of the copyright owner. Features and specifications are subject to change without prior notice. Codex and its product names are trademarks or registered trademarks of Codex. E & OE. Copyright ©2019. Codex. All Rights Reserved. Document No. CD-CX.0001002.DS.US

CODEx<sup>®</sup>

Codex | 60 Poland Street | London | W1F 7NT | UK