

Capture Drive® 2.0

Designed and manufactured in England by Codex

codex

The Codex Capture Drive® 2.0 meets the requirements of the new generation of digital cinematography cameras. Designed around the latest PCIe-based flash storage to deliver the fastest solid-state media available for professional media applications, it feeds seamlessly into Codex's industry standard workflows via the Codex Vault and Codex Capture Drive® 2.0 Dock.

Codex Capture Drive® 2.0 combines ultra-high performance solid-state storage with production reliability in a compact package.



KEY FEATURES

- > Up to 2TB of memory delivering up to 20 Gb/s bandwidth.
- > Optimised for performance.
- > Advanced thermal design.
- > Engineered to the highest performance standards.

SPECIFICATIONS

Interface	PCIe	
Capacity	Up to 2TB	
Dimensions [W x D x H]	61 x 110 x 16.2mm (2.4 x 4.3 x 0.6")	
Weight	200g	
Operating Temperature	0°C ~ 70°C (32°F ~ 158°F)	
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)	
Operating Relative Humidity	5 to 95% (non-condensing)	
Power Consumption (Active)	22W max	
Transfer Speed	Up to 20Gb/s	
Insertion/Removal Durability	10,000 actions	
Shock Resistance	(1/2 sine pulse, 0.5ms) - 1500G	
Vibration Resistance	(7 ~ 800Hz)- 3.08 Grms	
Warranty	1 year limited warranty	
Product Code	CDX-37018 (1TB)	CDX-37020 (2TB)

For further information on Codex Media, please go to codexdigital.com/products/media